



BAP Dual Pol. LET RET Antenna

Vertical Pattern (2500MHz)

Horizontal Pattern (2500MHz)


Electrical Parameters	BAP2700-65S-14DRE-B
Frequency range	2300~ 2700MHz
Gain	14dBi
Polarization	Dual, slant $\pm 45^\circ$
Isolation between ports	≥ 28 dB
Vertical plane -3dB beamwidth	18°
Horizontal plane -3dB beamwidth	65°
First upper sidelobe suppression	≥ 15 dB
VSWR	$\leq 1.5:1$
Front to back ratio	>30 dB@ $180^\circ \pm 30^\circ$
Max CW power per port	250W
Cross-Polarization Ratio	>20 dB@main direction, >10 @ $\pm 60^\circ$
IMD performance(2x43dBm)	≤ -150 dBc
Electrical downtilt range	14 ~ 27°
Connector type	DIN -F
External RCU interface/Number	AISG2.0/2
Mechanical Parameters	Specification
Rated wind speed	200km/hr
Dimensions H x W x D	825x153x86 mm
Packed size H x W x D	910x240x235 mm
net weight (with mounting hardware)	6.5 kg
Operating temperature	Min -40°C Max +60 °C
Radome material	FRP or UV Stable PVC
Performance	Specification
Materials:	All internal parts corrosion resistant. All antenna fasteners stainless steel. Bracket assemblies fully galvanized. Radome surface treated for maximum UV protection.
Mounting:	Available with either fixed brackets (non-adjustable) or mechanically adjustable bracket assemblies. Please specify when ordering.
Grounding:	Lower bracket assembly DC ground.
Connections:	Remote control electrical downtilt connections are in accordance with AISG standards

Eyecom company policy is one of continuing improvement, therefore we reserve the right to change this specification without notice.

*Built-in RCU version available